

# FIBRANgyps GLUE



## Product Description

Gypsum-based high density adhesive, in powder to be mixed with water for manual.  
Application, CE marked according to EN 14496

## Applications

To be used for fixing plasterboards on walls and coupling plasterboards with insulating materials.

Features	U. M.	Value	Standard
Reaction to fire	Class	A1	EN 13501-1
Workable time	min	90	-
Setting time	min	480	-
Preparation	-	preferably mechanical	-
Rating water/powder	-	100/160	-

## Storage and Application

Store in a cool, dry, ventilated and protected area. Use within 12 months from the date of production. Do not use at temperatures below + 5 ° C and above + 35 ° C.  
Apply on plasterboard, coupled panels (plasterboard with FIBRANxps or EPS insulation panels) with plots.  
Apply on coupled panels, plasterboard with FIBRANgeo panels, with stripes and plots.

FIBRAN reserves the right to alter or amend product specifications without notice. The information included in this publication is correct to the best of our knowledge at the time of printing. Whilst FIBRAN will endeavor to ensure publications are up to date, it is the user's responsibility to check with the company the validity of the information prior to materials' use. For more information visit the web site [www.fibran.it](http://www.fibran.it).

Date 31/07/2018

FIBRAN S.p.A. via Fiasella 5/11 16121 GENOVA Italy - ph. +39 010 25466.1 fax +39 010 25466.949 - [www.fibran.it](http://www.fibran.it) - [tech@fibran.it](mailto:tech@fibran.it)