

# FIBRANgyps JF READYMIX



## Product Description

FIBRANgyps JF READYMIX compound provides high performance and good open time, for bedding tapes and finishing joints in drywall partitions and ceilings. Ready-mixed for quick and easy application, lightened by 25% compared with traditional joint filler, very elastic and soft.

## Applications

High-performance and multi-task compound used for embedding joint tape, finishing drywall, and hand-applying simple texturing. It is also ideal for skim coating gypsum panel surfaces, laminating gypsum panels in multi-layer partitions and ceilings, and repairing small cracks in drywall

Features	U. M.	Value	Standard
Reaction to fire	Class	A1	EN 13501-1
Setting time	h	12	-
Preparation	-	Manual or mechanical	-
Surrender on plasterboard	-	38,3 l/100 m <sup>2</sup>	-

## Storage and Application

Store in a cool, dry, ventilated and protected area. Use within 12 months from the date of production. Do not use at temperatures below + 5 ° C and above + 35 ° C.

FIBRAN reserves the right to alter or amend product specifications without notice. The information included in this publication is correct to the best of our knowledge at the time of printing. Whilst FIBRAN will endeavor to ensure publications are up to date, it is the user's responsibility to check with the company the validity of the information prior to materials' use. For more information visit the web site [www.fibran.it](http://www.fibran.it).

Date 31/07/2018

FIBRAN S.p.A. via Fiasella 5/11 16121 GENOVA Italy - ph. +39 010 25466.1 fax +39 010 25466.949 - [www.fibran.it](http://www.fibran.it) - [tech@fibran.it](mailto:tech@fibran.it)