

FIBRANgyps JF SUPER



Product Description

Joint filler in powder with excellent workability, high resistance to bending and compression, minimal shrinkage, for grouting of plasterboard with high mechanical and surface resistance.

Manual application, recommended as first, second and third hand.

Marked 4B CE with reinforcement tape according to UNI EN 13963: 2014.

Applications

Treatment and filling of joints of plasterboard coated with fiberglass or paper tape for high-resistance systems, for grouting of screw heads and for repairing damaged in small plaster parts or plasterboard..

It is also used in the installation of edge protection and in the finishing of internal corners with microperforated tape.

Particularly suitable for FIBRANgyps ID and SUPER plates.

Features	U. M.	Value	Standard
Reaction to fire	Class	A1	EN 13501-1
Workable time	min	50-60*	EN 13963
Setting time	min	70-80*	EN 13963
Performance	kg/m ²	0,39	
Preparation	-	Manual and mechanical mixing	-
Rating water/powder	-	1 l /1,7 kg	-

* indicative times, variable according to weather conditions

Storage and Application

Store in a cool, dry, ventilated and protected area. Use within 12 months from the date of production. Do not use at temperatures below + 5 ° C and above + 35 ° C.

FIBRAN reserves the right to alter or amend product specifications without notice. The information included in this publication is correct to the best of our knowledge at the time of publishing. Whilst FIBRAN will endeavor to ensure publications are up to date, it is the user's responsibility to check with the company the validity of the information prior to materials' use. For more information visit the web site www.fibran.it.

05/11/2019