

FIBRANgyps TECNO H



Product Description

FIBRANgyps TECNO H is a prefabricated panel composed of water-repellent fiber-reinforced gypsum, characterized by a male-female joint on the perimeter edges and by a turquoise colour, CE marked according to UNI EN 15283-2.

FIBRANgyps TECNO H is incombustible Euroclass A1.

Applications

Suitable for the construction of internal partitions, lining walls and ceilings in humidity areas.

For partitions and/or lining walls in standard humidity areas it is recommended to use FIBRANgyps TECNO H (hydro) panels for the first row.

It must be installed with the special gypsum based glue/finishing FIBRANgyps FT3H, FIBRANgyps SCREW, FIBRANprofiles FT1718, and other system accessories. For more details, see the FIBRAN catalogue n°516.

Characteristic	U. M.	Value	Test method
Edges	-	Male / Female	-
Length	mm	1200	-
Width	mm	600 / 700	-
Density	kg/m ³	960	-
Thermal conductivity	W/m K	$\lambda_d = 0,35$	EN 15283-2
Fire reaction	Euroclass	A1	EN 1351-1
Specific heat capacity	MJ/kg	0,58	-
Water vapour permeability coefficient	-	$\mu = 6,3$	EN 10456
pH	-	7/8	-
Water absorption after 24 hours in immersion	%	W=26	-

Product code	Weight [kg/m ²]	Thickness [mm]	Length [mm]	Width [mm]
PGEFT2560IDROGR	24	25	1200	600
PGEFT2570IDROGR	24	25	1200	700

Storage: pallets must be stored away from rain, protected from knocks and damage.
For more information download the catalogue from the website www.fibran.it