

# FIBRANgyps TECNO



## Product Description

**FIBRANgyps TECNO** is a prefabricated panel composed of fiber-reinforced gypsum, characterized by a male-female joint on the perimeter edges, CE marked according to UNI EN 15283-2. It does not emit polluting substances, it has obtained the **A + classification** according to the EN ISO16000-09. FIBRANgyps TECNO is incombustible **Euroclass A1**.

## Applications

Suitable for the construction of internal partitions, lining walls and ceilings.

For partitions and/or lining walls it is recommended to use FIBRANgyps TECNO H (hydro) panels for the first row.

It must be installed with the special gypsum based glue/finishing FIBRANgyps FT3 or/and FT3H, FIBRANgyps SCREW, FIBRANprofiles FT1718. and other system accessories. For more details, see the FIBRAN catalogue n°516.

Characteristic	U. M.	Value	Test method
Edges	-	Male / Female	-
Length	mm	1200	-
Width	mm	600 / 700	-
Density	kg/m <sup>3</sup>	960	-
Thermal conductivity	W/m K	$\lambda_d = 0,35$	EN 15283-2
Fire reaction	Euroclass	A1	EN 13501-1
Specific heat capacity	MJ/kg	0,58	-
Water vapour permeability coefficient	-	$\mu = 5,6$	EN 10456
pH	-	7/8	-

Product Code	Weight [kg/m <sup>2</sup> ]	Thickness [mm]	Length [mm]	Width [mm]
PAFT2560GR	24	25	1200	600
PAFT2570GR	24	25	1200	700

**Storage:** pallets must be stored away from rain, protected from knocks and damage.  
For more information download the catalogue from the website [www.fibran.it](http://www.fibran.it)